

Attorney's Docket No. K&A 21-0775
Client's Docket No. SAM1274

APPLICATION

FOR UNITED STATES LETTERS PATENT

SPECIFICATION

TO ALL WHOM IT MAY CONCERN:

BE IT KNOWN THAT I, **BYRON K. MULLER, JR.**, a citizen
of UNITED STATES OF AMERICA, have invented a new and useful
URINE BAG CLEANING MACHINE of which the following is a
specification:



URINE BAG CLEANING MACHINE

5

BACKGROUND OF THE INVENTION

Field of the Invention

10 The present invention relates to urine bag cleaning apparatuses and more particularly pertains to a new urine bag cleaning machine for cleaning and sanitizing urine collection bags.

15 Description of the Prior Art

20 The use of urine bag cleaning apparatuses is known in the prior art. U.S. Patent No. 5,503,633 describes an astomy bag cleaning apparatus for the cleaning of an ostomy bag worm by and astomy patient. Another type of urine bag cleaning apparatus is U.S. Patent No. 4,995,410 having an astomy cleaning and receptacle replacement station for storing, cleaning and replacing astomy equipment. U.S. Patent No. 4,766,622 describes a peritoneal waste discharge system including a disinfectant storage chamber. U.S. Patent No. 4,763,678 describes a cleaning apparatus for elongated enclosed channel devices. U.S. Patent No. 6,103,189 describes a method of removing microbial contamination. U.S. Patent No. 6,068,817 describes a method for sterilizing an interior of an article with a diffusion-restricted area.

While these devices fulfill their respective, particular objectives and requirements, the need remains for a device that is superior in it's cleaning ability.

5

SUMMARY OF THE INVENTION

The present invention meets the needs presented above by
10 utilizing a 140-horsepower motor and 5000 CMF pump and dual filtration to provide a fast and effective cleaning process.

Still yet another object of the present invention is to provide a new urine bag cleaning machine that would be portable and easy
15 to use. The cleaning process would utilize conventional laundry detergent.

Even still another object of the present invention is to provide a new urine bag cleaning machine that would save the user
20 money by effectively cleaning and sanitizing the bags including disposable and reusable versions.

To this end, the present invention generally comprises a housing that has an interior space. A pump is positioned in the
25 interior space. A tank is positioned in the interior space. A conduit is positioned in the interior space and is environmentally coupled to the pump and the tank. A filter system is operationally coupled to the water tank for filtering a fluid for passing through the conduit. An influent manifold is positioned in the interior
30 space and environmentally coupled to the pump. An exfluent manifold is positioned in the interior space and is environmentally coupled to the tank. The influent manifold and the exfluent

manifold is substantially aligned apertures whereby the influent and exfluent manifolds are adapted for coupling to opposite ends of a urine bag to form a closed system for passing the fluid through the urine bag whereby the urine bag is cleansed.

5

There has thus been outlined, rather broadly, the more important features of the invention in order that the detailed description thereof that follows may be better understood, and in order that the present contribution to the art may be better appreciated. There are additional features of the invention that

10

will be described hereinafter and which will form the subject matter of the claims appended hereto.

The objects of the invention, along with the various features of novelty which characterize the invention, are pointed out with particularity in the claims annexed to and forming a part of this disclosure.

15

BRIEF DESCRIPTION OF THE DRAWINGS

20

The invention will be better understood and objects other than those set forth above will become apparent when consideration is given to the following detailed description thereof. Such description makes reference to the annexed drawings wherein:

25

Figure 1 is a perspective view of a new urine bag cleaning machine according to the present invention.

Figure 2 is a block diagram view of the present invention.

30

DESCRIPTION OF THE PREFERRED EMBODIMENT

With reference now to the drawings, and in particular to Figures 1 through 2 thereof, a new urine bag cleaning machine
5 embodying the principles and concepts of the present invention and generally designated by the reference numeral 10 will be described.

As best illustrated in Figures 1 through 2, the urine bag
cleaning machine 10 generally comprises a housing 12 that has an
10 interior space 14. A pump 16 is positioned in the interior space 14. A tank 18 is positioned in the interior space 14. A conduit 20 is positioned in the interior space 14 and is environmentally coupled to the pump 16 and the tank 18. A filter system 22 is operationally coupled to the conduit 20 for filtering a fluid for passing through
15 the conduit 20. An influent manifold 24 is positioned in the interior space 14 and environmentally coupled to the pump 16. An exfluent manifold 26 is positioned in the interior space 14 and is environmentally coupled to the tank 18. The influent manifold 24 and the exfluent manifold 26 is substantially aligned apertures 28
20 whereby the influent 24 and exfluent 26 manifolds are adapted for coupling to opposite ends of a urine bag 30 to form a closed system for passing the fluid through the urine bag 30 whereby the urine bag 30 is cleansed.

25 A drain 32 is operationally coupled to the tank 18 for permitting draining of the tank 18 when desired. A detergent reservoir 34 is environmentally coupled to the conduit 20 for introducing mixing a cleanser with the fluid to facilitate cleansing and deodorizing of the urine bag 30. The housing 12 has interior
30 walls 36 that divide the interior space 14 into a manifold chamber 38, a tank chamber 40, and a pump chamber 42. The pump 16 is

positioned in the pump chamber 42. The tank 18 is positioned in the tank chamber 40 and the influent 24 and exfluent 26 manifolds are substantially positioned in the manifold chamber 38. A cover member 44 is slidably engaged to the housing 12 for selectively
5 covering the pump chamber 42 and the tank chamber 40.

A lid 46 is pivotally coupled to the housing 12 for selectively covering the manifold chamber 38. The influent manifold 24 and the exfluent manifold 26 each has three selectively openable
10 apertures 28 for permitting cleansing of up to three urine bags 30 simultaneously. An electrical cord 48 is operationally coupled to the pump 16 whereby the pump 16 is adapted for electrical connection to an electrical outlet to power the pump 16. The
15 filtering system 22 includes a first filter 50 and a second filter 52 in series for filtering the fluid passing through the filtering system 22.

The filtering system 22 includes a first filter 50 and a second filter 52. The first filter 50 is coupled to the exfluent manifold 26
20 for filtering the fluid before it passes into the water tank 18. The second filter 52 is coupled to the conduit 20 for filtering the fluid before it passes into the pump 16. The second filter 52 is positioned between the water tank 18 and the detergent reservoir 34 for filtering the fluid before the cleanser is mixed into the fluid.

25 In use, the bag would be positioned within the unit, connecting to the water tubes at each bag's drain valve and adaptor valve. The machine would be appropriately sized to hold and clean two to three bags at one time.

With respect to the above description then, it is to be realized that the optimum dimensional relationships for the parts of the invention, to include variations in size, materials, shape, form, function and manner of operation, assembly and use, are deemed
5 readily apparent and obvious to one skilled in the art, and all equivalent relationships to those illustrated in the drawings and described in the specification are intended to be encompassed by the present invention.

10 Therefore, the foregoing is considered as illustrative only of the principles of the invention. Further, since numerous modifications and changes will readily occur to those skilled in the art, it is not desired to limit the invention to the exact construction and operation shown and described, and accordingly, all suitable
15 modifications and equivalents may be resorted to, falling within the scope of the invention.